

Ultra-wide Zoom Lenses

Canon EF Lens	Pricing	Drive System	Angle of View (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF-M11-22mm f/4-5.6 IS STM	S\$589	Stepping motor (STM)- driven lead screw + rack system	102°10'– 63°30'	9 - 12	0.15/0.49	72.9	220	EW-60E	55	E-55	LP814
EF-S10-18mm f/4.5-5.6 IS STM	S\$429	Lead screw and rack system driven by stepping motor	107°30' - 74°20'	11-14	0.22/0.72	72	240	EW-73C	67	E-67 II	LP1116
EF-S10-22mm f/3.5-4.5 USM	S\$959	Ring-type USM*2	107°30' - 63°30'	10 - 13	0.24/0.8	89.8	385	EW-83E	77	E-77U / E-77 II	LP1319
EF-S18-200mm f/3.5-5.6 IS	S\$1,129	micro motor	74°20' - 7°50'	12 - 16	0.45/1.5 - infinity	102	595	EW-78D	72	E-72	LP1116
EF11-24mm f/4L USM	S\$4,499	Focusing cam system by ring USM drive	126°05' - 84°00'	11-16	11 in. / 0.28m	132	1180	Integrated petal-type hood (integrated hood	Rear insert- type	11 -24	LP1424
EF16-35mm f/2.8L II USM	S\$2,519	Ring-type USM*1	108°10' - 63°	12 - 16	0.28/0.9	111.6	640	EW-88	82	E-82U	LP1319
EF16-35mm f/2.8L III USM	S\$3,599	Extension system by inner focusing with focusing cam	108°10' - 63°00'	11 - 16	0.28/0.92	127.5	790	EW-88D	82	E-82 II	LP1222
EF16-35mm f/4L IS USM	S\$1,579	Focusing cam system by ring USM drive	108°10' - 63°	13 - 16	0.28/0.92	112.8	615	EW-82	77	E-77 II	LP1219
EF17-40mm f/4L USM	S\$1,239	Ring-type USM*2	104° - 57°30'	9 -12	0.28/0.9	96.8	475	EW-83E	77	E-77U / E-77 II	LP1319

Standard Zoom Lenses

Canon EF Lens	Pricing	Drive System	Angle of View (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF-S15-85mm f/3.5-5.6 IS USM	S\$1,199	Ring USM	74°10' - 15°25'	12 - 17	0.35/1.1 - infinity	87.5	575	EW-78E	72	E-72U	LP1116
EF-S17-55mm f/2.8 IS USM	S\$1,299	Ring-type USM*2	78°30' - 27°50'	12 - 19	0.35/1.2	110.6	645	EW-83J	77	E-77U / E-77 II	LP1219
EF-S17-85mm f/4-5.6 IS USM	S\$1,199	Ring-type USM*2	78°30' - 18°25'	12 - 17	0.35/1.2	92	475	EW-73B	67	E-67U	LP1116
EF-S18-135mm f/3.5-5.6 IS	S\$729	micro motor	64°30' - 9°30'	12 - 16	0.45m/1.5 - infinity	101	455	EW-73B	67	E-67U	LP1116
EF-S18-135mm f/3.5-5.6 IS STM	S\$849	Lead screw and rack system driven by stepping motor	11°30' - 74°20'	12 - 16	0.39/1.3	96	480	EW-73B	67	E-67	LP1116
EF-S18-135mm f/3.5-5.6 IS USM	S\$899	Nano USM motor	74°20'~11°30'	12 - 16	0.39/1.3	96	515	EW-73D	67	E-67 II	LP1116
EF-S18-55mm f/3.5-5.6 IS	S\$369	MM*3	74°20' - 27°50'	9 - 11	0.25/0.8	70	200	EW-60C	58	E-58	LP814
EF-S18-55mm f/3.5-5.6 IS STM	S\$389	STM	74°20' - 27°50'	11-13	0.25/0.82	75.2	205	EW-63C	58	E-58 II	LP1016
EF24-105mm f/4L IS II USM	S\$1,999	Ring USM-driven focus cam ring	84°00' - 23°20'	12 - 17	0.45/1.5	118	795	EW-83M	77	E-77 II	LP1219
EF24-105mm f/4L IS USM	S\$1,699	Ring-type USM*2	84° - 23°20'	13 - 18	0.45/1.5	107	670	EW-83H	77	E-77U / E-77 II	LP1219
EF24-70mm f/2.8L II USM	S\$3,059	Ring USM	84° - 34°	13 - 18	0.38/1.25 (wide/tele)	113	805	EW-88C	82	E-82 U	LP1219
EF24-70mm f/2.8L USM	S\$2,699	Ring-type USM*2	84° - 34°	13 - 16	0.38/1.3	123.5	950	EW-83F	77	E-77U	LP1219
EF24-70mm f/4L IS USM	S\$1,779	Ring USM	84° - 34°	12 - 15	0.2/0.6 (Macro/Macro)	93	600	EW-83L	77	E-77II	LP1219
EF28-135mm f/3.5-5.6 IS USM	S\$899	Ring-type USM*2	75° - 18°	12 - 16	0.5/1.6	96.8	540	EW-78B II	72	E-72U	LP1116
EF28-300mm f/3.5-5.6L IS USM	S\$3,779	Ring-type USM*2	75° - 8°15'	16 - 23	0.7/2.3	184	1,670	EW-83G	77	E-77U / E-77 II	LZ1324
EF-M18-55mm f/3.5-5.6 IS STM	S\$469	Stepping motor-driven lead screw + rack system	74°20' - 27°50'	11 - 13	0.25/0.82	61	210	EW-54	52	E-52II	LP814

Telephoto Zoom Lenses

Canon EF Lens	Pricing	Drive System	Angle of View (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF-M55-200mm f/4.5-6.3 IS STM	S\$499	Lead screw and rack system driven by stepping motor drive pulse count	27°50' - 7°50'	11 - 17	1.0/3.28	86.5	260	ET-54B	52	E-52 II	LP816
EF-S55-250mm f/4-5.6 IS STM	S\$399	Lead screw and rack system driven by stepping motor	27°50' - 6°15'	12 - 15	0.85/2.79	111.2	375	ET-63	58	E-58 II	LP1019
EF100-400mm f/4.5-5.6L IS II USM	S\$3,299	Focusing cam system by ring USM drive	24° – 6°10'	16 - 21	0.98/3.2	193	1,570	ET-83D	77	E-77 II	LZ1326
EF200-400mm f/4L IS USM Extender 1.4x	S\$16,599	Ring-type USM	12° - 6°10'	20 - 25	2/6.6	128	3,620	ET-120 (WII)	52	E-145C	200 – 400
EF70-200mm f/2.8L IS II USM	S\$3,329	Ring-type USM*2	34° - 12°	23 - 19	1.2/3.9	199	1,490	ET-87	77	E-77U	LZ1326
EF70-200mm f/2.8L USM	S\$2,149	Ring-type USM	34° - 12°	15 - 18	1.5/5.0	193.6	1,310	ET-83 II	77	E-77U / E-77 II	LZ1324
EF70-200mm f/4L IS USM	S\$1,899	Ring-type USM*2	34° - 12°	15 - 20	1.2/3.9	172	760	ET-74	67	E-67U	LP1224
EF70-200mm f/4L USM	S\$1,049	Ring-type USM*2	34° - 12°	13 - 16	1.2/3.9	172	705	ET-74	67	E-67U	LP1224
EF70-300mm f/4-5.6 IS II USM	S\$\$ 829	Direct drive provided by Nano USM	34° - 8°15'	12 - 17	1.20/3.94	145.5	710	ET-74B	67	E-67 II	LP1222
EF70-300mm f/4-5.6L IS USM	S\$2,129	Ring-type USM	34° - 8°15'	14 - 19	1.2/3.9	143	1,050	ET-73B	67	E-67U	LP1424
EF70-300mm f/4.5-5.6 DO IS USM	S\$2,399	Ring-type USM*2	34° - 8°15'	12 - 18	1.4/4.9	99.9	720	ET-65B	58	E-58U	LP1116
EF75-300mm f/4-5.6 III	S\$299	MM*3	32°11' - 8°15'	9 - 13	1.5/4.9	122	480	ET-60	58	E-58 / E-58 II	LP1019

Wide-angle Lenses

Canon EF Lens	Pricing	Drive System	Angle of View (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF-M22mm f/2.0 STM	S\$ 379	Gear drive by stepping motor	63°30′	6 - 7	0.15/0.49	23.7	105	EW-43	43	E-43	LP811
EF-M22mm f/2.0 STM (Silver)	"		"	"	"	"	"	"	"	"	"
EF-S24mm f/2.8 STM	S\$ 219	Stepping motor-gear drive	59°10′	6 - 5	0.16/0.52	22.8	125	ES-52	52	E-52II	LP811
EF14mm f/2.8L II USM	S\$3,329	Ring-type USM*2	114°	11 - 14	0.2/0.7	94	645	Built-in	Gelatin	Exclusive	LP1016
EF20mm f/2.8 USM	S\$899	Ring-type USM*2	94°	9 - 11	0.25/0.8	70.6	405	EW-75 II	72	E-72U	LP1214
EF24mm f/1.4L II USM	S\$2,459	Ring-type USM*2	84°	10 - 13	0.25/0.8	86.9	650	EW-83K	77	E-77U / E-77 II	LP1319
EF24mm f/2.8 IS USM	S\$1,199	Ring USM (IS Type)	84°	9 - 11	0.20/0.66	55.7	280	EW-65B	58	E-58U	LP1014
EF28mm f/1.8 USM	S\$889	Ring-type USM*2	75°	9 - 10	0.25/0.8	55.6	310	EW-63 II	58	E-58U	LP814
EF28mm f/2.8	S\$389	AFD	75°	5 - 5	0.3/1.0	42.5	185	EW-65 II	52	E-52	LP1011
EF28mm f/2.8 IS USM	S\$869	Ring USM (IS Type)	75°	7 - 9	0.23/0.75	51.5	260	EW-65B	58	E-58U	LP1014
EF35mm f/1.4L USM	S\$2,189	Ring-type USM*2	63°	9 - 11	0.3/1.0	86	580	EW-78C	72	E-72U	LP1214
EF35mm f/2 IS USM	S\$1,199	Ring-type USM	63°	8 - 10	0.24/0.79	62.6	335	EW-72	67	E-67II	LP1116

Standard & Medium Telephto Lenses

Canon EF Lens	Pricing	Drive System	Angle of View (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF100mm f/2 USM	S\$839	Ring-type USM*2	24°	6 - 8	0.9/3.0	73.5	460	ET-65 III	58	E-58U	LP1014
EF40mm f/2.8 STM	S\$299	Cam ring rotated to fixed positions by electric drive of gear system	57°30′	4 - 6	0.3/0.98	22.8	130	ES-52	52	E-52	LP811
EF50mm f/1.2L USM	S\$2,279		46°	6 - 8	0.45/1.5	65.5	590	ES-78	72	E-72U	LP1214
EF50mm f/1.4 USM	S\$589	Ring-type USM*2	46°	6 - 7	0.45/1.5	50.5	290	ES-71 II	58	E-58U / E-58 II	LP1014
EF50mm f/1.8 II	S\$159	MM*3	46°	5 - 6	0.45/1.5	41	130	ES-62 + ADP	52	E-52 / E-52 II	LP1014
EF50mm f/1.8 STM	S\$189	STM	46°	5 - 6	0.35 /1.15	39.3	160	ES-68	49	E-49	LP1014
EF85mm f/1.2L II USM	S\$3,099	Ring-type USM*2	28°30′	7 - 8	0.95/3.1	84	1,025	ES-79 II	72	E-72U	LP1219
EF85mm f/1.8 USM	S\$619	Ring-type USM*2	28°30′	7 - 9	0.85/2.8	71.5	425	ET-65 III	58	E-58U	LP1014

Telephoto Lenses

Canon EF Lens	Pricing	Drive System	Angle of View (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF135mm f/2.8 (with Softfocus)	S\$789	AFD	18°	6 - 7	1.3/4.3	98.4	390	ET-65 III	52	E-52	LP1016
EF135mm f/2L USM	S\$1,529	Ring-type USM*2	18°	8 - 10	0.9/3.0	112	750	ET-78 II	72	E-72U	LP1219
EF200mm f/2.8L II USM	S\$1,149	Ring-type USM*2	12°	7 - 9	1.5/4.9	136.2	765	ET-83B II	72	E-72U	LP1222
EF200mm f/2L IS USM	S\$8,899	Ring-type USM*2	12°	12 - 17	1.9/6.2	208	2,520	ET-120B	52 drop-in	E-145B	Lens Case 200
EF300mm f/4L IS USM	S\$2,149	Ring-type USM*2	8°15′	11 - 15	1.5/4.9	221	1,190	Built-in	77	E-77U / E-77 II	LZ1128

Fish-eye Zoom Lenses

Canon EF Lens	Pricing	Drive System	Angle of View (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF8-15mm f/4L Fisheye USM	S\$1,999	Ring-type USM*1	180° - 175°30′	11 - 14	0.15/0.49	83	540	EW-77	Real Gel Holder	Lens Cap 8-15	LP1219

Super Telephoto Lenses

Canon EF Lens	Pricing	Drive System	Angle of view (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF300mm f/2.8L IS II USM	S\$9,699	Ring-type USM*2	8°15′	12 - 16	2.0/6.6	248	2,400	ET-120	52 drop-in	E-145C	Lens Case 300B
EF400mm f/2.8L IS II USM	S\$15,299	Ring-type USM*2	6°10′	12 - 16	2.7/8.86	343	3,850	ET-155	52 drop-in	E-180D	Lens Case 400C
EF400mm f/4 DO IS USM	S\$10,999	Ring-type USM*2	6°10′	13 - 17	3.5/11.5	232.7	1,940	ET-120	52 drop-in	E-145	Lens Case 400B
EF400mm f/4 DO IS II USM	S\$10,999	Ring-type USM*2	6°10′	18 - 12	3.3/10.83	232.7	2,100	ET-120 (WII)	52 drop-in	E-145C	Lens Case 400D
EF400mm f/5.6L USM	S\$1,979	Ring-type USM*2	6°10′	6 - 7	3.5/11.5	256.5	1,250	Built-in	77	E-77U / E-77 II	LZ1132
EF500mm f/4L IS II USM	S\$13,999	Ring-type USM	5°	12 - 16	3.7/12.14	383	3,190	ET-138 (WII)	52 drop-in	E-163B	Lens Case 500B
EF500mm f/4L IS USM	S\$12,999	Ring-type USM*2	5°	13 - 17	4.5/14.8	387	3,870	ET-138	52 drop-in	E-163	Lens Case 500
EF600mm f/4L IS II USM	S\$17,299	Ring-type USM	4°10′	12 - 16	4.5/14.77	448	3,920	ET-160 II	52 drop-in	E-185B	Lens Case 600B
EF800mm f/5.6L IS USM	S\$19,699	Ring-type USM*1	3°5′	14 - 18	6/19.69	461	4,500	ET-155	52 drop-in	E-180C	Lens Case 800
Extender EF 1.4xIII	S\$669	-	-	3 - 7	-	27.2	225	-	-	Extender Cap E II	LP811
Extender EF 2xIII	S\$669	-	-	5 - 9	-	52.7	325	-	-	Extender Cap E II	LP811

Macro Lenses

Canon EF Lens	Pricing	Drive System	Angle of view (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
EF-S60mm f/2.8 Macro USM	S\$749	Ring-type USM	24°30′	8 - 12	0.2	69.8	335	ET-67B	52	E-52U	LP1016
EF100mm f/2.8 Macro USM	S\$929	Ring-type USM*2	24°	8 - 12	0.31/1.0	118.6	580	ET-67	58	E-58U	LP1219
EF100mm f/2.8L Macro IS USM	S\$1,399	Ring-type USM*2	19.8°	12 - 15	0.3/0.99	123	625	ET-73	67	E-67U	LP1219
EF180mm f/3.5L Macro USM	S\$2,219	Ring-type USM*2	13°40′	12 - 14	0.45/1.5	186.6	1,090	ET-78 II	72	E-72U	LZ1324
Life-size Convertor EF	S\$499	-	-	3 - 4	0.24/0.8	34.9	160	-	-	R-F-3	LP811
MP-E65mm f/2.8 1-5x Macro Photo	S\$1,739	-	18°40′	8 - 10	0.24/0.8	98	570	Exclusive	58	E-58	LP1216

Tilt-shift Lenses

Canon EF Lens	Pricing	Drive System	Angle of view (Diagonal)	Construction	Closest Focusing Distance (m/ft)	Length (mm)	Weight (g)	Lens Hood	Filter Size (mm)	Lens Cap	Case
TS-E17mm f/4L	S\$3,329	-	93°	12 - 18	0.25/0.82	106.7	820	-	-	LENS Cap 17	LP1219
TS-E24mm f/3.5L II	S\$2,929	Manual	74°	11 - 16	0.21/0.69	106.9	780	EW-88B	82	E-82	LP1319
TS-E45mm f/2.8	S\$2,299	-	27°	9 - 10	0.4/1.3	90.1	645	EW-79B II	72	E-72	LP1216
TS-E90mm f/2.8	S\$2,299	-	27°	5 - 6	0.5/1.6	88	565	ES-65 III	58	E-58	LP1016

Speedlite Flashes (Emits the perfect amount of light for your shoot)

Speedlite Flashes		Pricing
Macro Ring Lite MR-14EX		S\$849
Macro Ring Lite MR-14EX II		S\$849
Macro Twin Lite MT-24EX		S\$1,439
Release Cable SR-N3		S\$79
Speedlite 270EXII		S\$239
Speedlite 320EX	Battery Size: 2 x "AA" (Not Included)	S\$349
Speedlite 430EX III-RT	Battery Size: 2 x "AA" (Not Included)	S\$419
Speedlite 580EX II	Battery Size: 4 x "AA" (Not Included)	S\$899
Speedlite 600EX-RT		S\$749
Speedlite 90EX		S\$159
Speedlite Transmitter ST-E3-RT		S\$469

*1 AF can be used only with the center measuring point when using the EOS-IV/HS, EOS-3, EOS-1Ds Mark II, EOS 1Ds, EOS-1D Mark II N, EOS-1D Mark II, EOS-1D, EOS 5D. With other EOS cameras only manual focus is available.

*2 Equipped with a full-time mechanism.

*3 Micro motor.

*4 Image circle 58.6mm.