

Ceiling Mounting Kit CM10-VB

- This accessory is used for mounting camera to ceiling, supporting connection to junction box as well and $\frac{3}{4}$ " NPS conduit pipe.
- Dimension: (H x W x D)
178 x 134 x 253 mm
(7.01 x 5.28 x 9.96 in.)
- Weight: Approx. 2300g (5.08lb.)
- Impact Resistance: IK10 (20J)
- Compatible with Canon VB-R10VE and VB-R11VE



Wall Mounting Kit WM10-VB

- This accessory is used to connect camera to the wall, supporting connection to junction box as well as $\frac{3}{4}$ " NPS conduit pipe.
- Dimension: (H x W x D)
234 x 134 x 245 mm
(9.21 x 5.28 x 9.65 in.)
- Weight: Approx. 2300g (5.08lb.)
- Impact Resistance: IK10 (20J)
- Compatible with Canon VB-R10VE and VB-R11VE



1.5-Inch Pipe Adapter PA10-15-VB

- This accessory is an adapter used to connect camera to 1.5 Inch NPS pipe.
- Dimension: (H x W x ϕ)
102 x 68 x ϕ 60 mm
(4.02 x 2.68 x ϕ 2.36 in.)
- Weight: Approx. 200g (7.1oz)
- Compatible with Canon VB-R10VE and VB-R11VE



Tinted Capsule DU10-S-VB

- This accessory is a replacement smoked capsule
 - Dimension: (ϕ x H)
 $\phi 179 \times 108$ mm
($\phi 7.05 \times 4.25$ in.)
- Weight: Approx. 145g (5.2oz.)
- Compatible with Canon VB-R10VE, VB-R11VE and VB-R11



AC Adapter

PA-V18

(Optional)

■Dimension: (H x W x D) 32 x 60 x 130 mm (1.26 x 2.36 x 5.12 in.), excluding projections.

Weight: Approx. 245 g (8.7 oz.)
(excluding power cable)

■Input: 100 – 240 V AC, 50/60 Hz

■Output: 13.1 V DC Max. 1.8 A
(temperature: -10°C – +35°C (+14°F – +95°F)), 13.1 V DC Max. 1.1 A
(temperature: -10°C – +50°C (+14°F – +122°F))

■Operating Temperature: -10°C – +50°C (+14°F – +122°F)

Humidity: 5% – 85% (without condensation)

■Compatible with Canon VB-M42/B, VB-M620D, VB-M620VE, VB-M720F, VB-H43/B, VB-H630D, VB-H630VE, VB-H730F, VB-R11, VB-R10VE, VB-R11VE, VB-M641V, VB-M641VE, VB-M741LE

