

High performance office communication platform

The imageRUNNER ADVANCE C5500i Series delivers high performance and quality colour output for demanding office environments. These intelligent multifunctionals enhance productivity through improved document workflows and intuitive user experience. With added security features, the imageRUNNER ADVANCE C5500i is an essential device for any modern day working environment.

Workflow Efficiency

- Intuitive user interface with a large, colour touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Intelligent feeder allows effortless, rapid scanning with features like multi-sheet feed detection and skip blank originals.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile and flexible working styles allow workers to capture or print documents with the Canon Print Business app.
- Scan and convert documents through a single-pass duplexing document feeder that holds up to 150 originals.
- Intelligent Recovery wakes device from sleep mode when user is approaching device via motion sensor technology.
- Various finishing functions such as Staple-on-Demand, ECO-Staple, saddle stitch, double/corner stapling and foldings are available as an option.

Cost Management

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, encourages cost recovery, and can help save money on paper and toner.
- Tight integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT resolving issues.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.



Security

- Control who has access to the device with Picture Login authentication.
- Prevent unauthorised distribution of sensitive information with an array of standard and optional document security features.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Secure Print and Mailbox enhance document confidentiality.



Device and Fleet Management Efficiency

- Synchronise personalised user settings across multiple devices through My ADVANCE Sync.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Standard PCL and optional Adobe PostScript print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.

Reliability

- V² (Vivid & Vibrant) imaging technology ensures high quality printouts that impress time after time.
- Supreme transferability of toner and stable reproduction of colours onto a wide range of media, even at large volumes.
- State-of-the-art imaging technologies and toner allow for consistently striking images with real 1,200 dpi. print resolution.
- Designed to achieve maximum uptime with intuitive user walkthrough videos and status notifications, to help keep supplies replenished.
- Maximum paper capacity of 6,350 sheets reduces downtime.

Sustainability

- Fusing technologies, CS toner, and innovative sleep mode features help lower overall energy consumption.
- Minimise waste with 2-sided printing, secure printing, and the ability to hold print jobs, preview them and change print settings at the device, achieving the desired results at the first time of printing.
- Incorporates sustainable design, with the use of recycled materials and bio-based plastic, and a focus on minimising environmental impact.
- Consumes as little as 0.9W in sleep mode.

Configuration

BOOKLET FINISHER-Y1

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports ECO-Staple 4 sheets (80 gsm) and Staple-on-Demand 50 sheets (90 gsm)
- Supports optional internal 2/3 and 2/F4 Hole Puncher Unit-A1



STAPLE FINISHER-Y1

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Staple 4 sheets (80 gsm) and Staple-on-Demand 50 sheets (90 gsm)
- Supports optional internal 2/3 and 2/F4 Hole Puncher Unit-A1



INNER 2 WAY TRAY-J1

- 2-tray, 350-sheet capacity
- Separates copies, prints and faxes
- Adds a second internal output tray



BUFFER PASS UNIT-L1

- Inner tray, 100-sheet capacity
- Transports paper to external finisher



INNER FINISHER-H1

- 2-tray, 545-sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Staple 4 sheets (80 gsm) and Staple-on-Demand 40 sheets (80 gsm)
- Supports optional Inner 2/3 Hole Puncher-B1 and Inner 2/F4 Hole Puncher-B1



IC CARD READER BOX-C1



COPY TRAY-J2

- 100-sheet capacity



PAPER DECK UNIT-F1

- Supports A4 and B5
- Media weight 52-256 gsm
- 2,700 sheets (80 gsm)



ColorPASS-GX500*

- PDL MEMORY SYSTEM
- PS/APPE
 - 4GB/1TB
 - Fiery FS200 Pro



imagePASS-PS1

- PCL/PS
- 2GB/500GB
- Fiery FS200

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm(TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI™ management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation

*Applicable to iR-ADV C5550i/C5560i only



CASSETTE FEEDING UNIT-AM1

- Supports up to A3
- Media weight 52-256 gsm
- 2 x 550 sheets (80 gsm)



HIGH CAPACITY CASSETTE FEEDING UNIT-A1

- Supports A4
- Media weight 52-256 gsm
- 2,450 sheets (80 gsm)

Main Unit

Type

Colour Laser Multifunctional

Core Function

Print, Copy, Scan, Send, Store and Optional Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1 inch TFT LCD WSVGA Colour Touchpanel

Memory

Standard: 4.0GB RAM

Hard Disk Drive

Standard: 250GB
Maximum: 1TB

Mirroring Hard Disk Drive

Optional 250GB, 1TB

Interface Connection

Network Standard: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Others Optional: NFC, Bluetooth
Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)
Optional: Serial Interface, Copy Control Interface

Paper Capacity (80gsm)

Standard: 1,200 Sheets
Maximum: 6,350 Sheets

Paper Sources (80gsm)

Standard: Two 550-sheet Paper Cassettes
100-sheet Multi-purpose tray
Optional: CASSETTE FEEDING UNIT-AM1:
Two 550-sheet Paper Cassettes
HIGH CAPACITY CASSETTE FEEDING UNIT-A1:
2,450-sheet Paper deck
PAPER DECK UNIT-F1:
2,700-sheet Paper deck
Maximum: 6,350 Sheets

Paper Output Capacity (80gsm)

Standard: 250 Sheets
Maximum: 3,450 Sheets (with External Finisher and Copy Tray)

Finishing Capabilities

Standard: Collate, Group
With Inner Finisher: Collate, Group, Offset, Staple, *Hole Punch,
ECO-Staple, Staple-on-Demand

*Necessary for INNER 2/3 HOLE PUNCHER-B1 or INNER 2/F4 HOLE PUNCHER-B1
With External Finisher: Collate, Group, Offset, Staple, **Booklet, *Hole
Punch, ECO-Staple, Staple-on-Demand
**Necessary for 2/3 HOLE PUNCHER UNIT-A1 or 2/F4 HOLE PUNCHER UNIT-A1
**BOOKLET FINISHER-Y1 only

Supported Media Types

Cassette 1: Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Transparency*,
Bond paper, Envelope, Letterhead

Cassette 2: Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Transparency*,
Tab paper, Bond paper, Envelope, Letterhead

CASSETTE FEEDING UNIT-AM1:

Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Transparency*,
Bond paper, Letterhead

HIGH CAPACITY CASSETTE FEEDING UNIT-A1:

Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Bond paper,
Letterhead

Multi-purpose tray:

Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Transparency*,
Tracing paper, Label, Tab paper, Bond paper,
Coated paper, Envelope, Letterhead, Labels

PAPER DECK UNIT-F1:

Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Bond paper,
Letterhead

*Use only A4 transparencies made especially for multi-functional device

Supported Media Sizes

Cassette 1: Standard size: A4, B5, A5, A5R
Custom Size: 98.0 mm x 148 mm to
297 mm x 215.9 mm

Cassette 2: Standard size: A3, B4, A4, A4R, B5, B5R, A5R,
Foolscap, India Legal, F4A,
Custom size: 98.0 mm x 182 mm to
304.8 mm x 457.2 mm

CASSETTE FEEDING UNIT-AM1:

Standard size: A3, B4, A4, A4R, B5, B5R, A5R,
Foolscap, India Legal, F4A,
Custom size: 98.0 mm x 182 mm to
304.8 mm x 457.2 mm

HIGH CAPACITY CASSETTE FEEDING UNIT-A1:

Standard size: A4

PAPER DECK UNIT-F1:

A4, B5

Multi-purpose tray:

Standard size: A3, B4, A4, A4R, B5, B5R, A5, A5R,
Foolscap, India Legal, F4A, Envelope
(No.10(COM10), Monarch, DL, ISO-C5)
Custom Size: 98.0 mm x 139.7 mm to
320 mm x 457.2 mm
Free Size: 98.0 mm x 139.7 mm to
320 mm x 457.2 mm

Supported Media Weights

Cassettes: 52 to 256 gsm
Multi-purpose tray: 52 to 300 gsm
Duplex: 52 to 220 gsm

Warm-up Time

*From Power On: 30 Seconds or Less

*Time between device power-on and when the start key is
enabled (print reservation)

From Deep Sleep Mode: 10 Seconds or Less

**Quick Startup Mode: 4 seconds

** If <Quick Startup Settings for Main Power> is set to "On", it takes 4 seconds until
the key operation on the touch panel display is available after turning on the
main power of the machine. Depending on the situations, the machine does
not startup quickly.

Dimensions (W x D x H) 620 mm x 742 mm x 950 mm

Installation Space (W x D) 943 mm x 1,176 mm
(when Multi-purpose tray Extended + Cassette Drawers open)

Weight* Approx. 143kg
*Including the toner bottle

Print Specifications

Printing Method

Colour laser beam printing

Print Speed iR-ADV C5560i: 60 ppm (A4)
32 ppm (A3)
iR-ADV C5550i: 50 ppm (A4)
27 ppm (A3)
iR-ADV C5540i: 40 ppm (A4)
22 ppm (A3)
iR-ADV C5535i: 35 ppm (A4)
18 ppm (A3)

Print Resolution

600 dpi x 600 dpi (Default), 1,200 dpi x 1,200 dpi)

Page Description Languages

UFRI II, PCL6 (Standard), Adobe PS 3 (Option)

Double Sided Printing

Automatic (Standard)

Direct Print

Direct printing available from USB memory key, Advanced box,
Remote UI and Web Access*
Supported File Types: PDF, TIFF, JPEG, XPS
*Only PDF print from websites is supported.

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andale Mono WT/J/K/S/T* (Japanese, Korean,
Simplified and Traditional Chinese), Barcode fonts**
*Requires optional PCL INTERNATIONAL FONT SET-A1
**Require optional BARCODE PRINTING KIT-D1
PS fonts: 136 Roman

Operating System

UFRI II: Server 2003/Server 2003 R2/Windows Vista/Server 2008/
Windows 7/Server 2008 R2/Windows 8/Server 2012/
Windows 8.1/Server 2012 R2/Windows 10, MAC OS X
(10.6.8 or later)

PCL: Server 2003/Server 2003 R2/Windows Vista/Server 2008/
Windows 7/Server 2008 R2/Windows 8/Server 2012/
Windows 8.1/Server 2012 R2/Windows 10

PS: Server 2003/Server 2003 R2/Windows Vista/Server 2008/
Windows 7/Server 2008 R2/Windows 8/Server 2012/
Windows 8.1/Server 2012 R2/Windows 10, MAC OS X
(10.6.8 or later)

PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later),
Windows Vista/Windows 7/Windows 8/Windows8.1/
Windows10

Copy Specifications

Copy Speed iR-ADV C5560i: 60 ppm (A4)
32 ppm (A3)
iR-ADV C5550i: 50 ppm (A4)
27 ppm (A3)
iR-ADV C5540i: 40 ppm (A4)
22 ppm (A3)
iR-ADV C5535i: 35 ppm (A4)
18 ppm (A3)

*First-Copy-Out Time (A4)

* 20 °C to 30 °C Environment

iR-ADV C5560i: Approx. 2.9 seconds or less (BW),
Approx. 4.5 seconds or less (CL)

iR-ADV C5550i: Approx. 3.5 seconds or less (BW),
Approx. 5.2 seconds or less (CL)

iR-ADV C5540i: Approx. 4.1 seconds or less (BW),
Approx. 6.1 seconds or less (CL)

iR-ADV C5535i: Approx. 4.9 seconds or less (BW),
Approx. 7.4 seconds or less (CL)

Copy Resolution

Reading: 600 dpi x 600 dpi
Printing: Up to 1,200 dpi x 1,200 dpi

Multiple Copies

Up to 999 copies

Copy Exposure

Automatic or Manual (11 Levels)

Magnification

25% - 400% (1% Increments)

Preset Reductions

25%, 50%, 61%, 70%, 81%, 86%

Preset Enlargements

115%, 122%, 141%, 200%, 400%

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

150 Sheets (80gsm)

Document Feeder Supported Media Sizes

A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R

Document Feeder Supported Media Weights

Single-sided scanning: 38* to 157 gsm (BW)
64 to 157 gsm (CL)
Double-sided scanning: 50 to 157 gsm (BW)
64 to 157 gsm (CL)

*Originals weighing from 38 g/m² to 42 g/m² are supported when scanning a
single original that has a width of 257 mm or larger.

Pull Scan Spec

Color Network ScanGear2. For both Twain and WIA

Supported OS: Windows Vista/7/8/8.1/10
Windows Server 2003/Server 2003 R2/Server
2008/Server 2008 R2/Server 2012/Server 2012 R2

Scan Resolution

100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi,
200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi

Platen Acceptable Originals

Platen: Sheet, Book, 3-Dimensional Objects
[Up to 2kg]

Feeder size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6

Scan Speed (A4)

Single-sided Scanning (BW) : 80 ipm (300pi)/80 ipm (600 dpi)
Single-sided Scanning (Colour) : 80 ipm (300pi)/60 ipm (600 dpi)
Double-sided Scanning (BW) : 160 ipm (300pi)/150 ipm (600 dpi)
Double-sided Scanning (Colour) : 160 ipm (300pi)/80 ipm (600 dpi)

Double sided scanning

2-sided to 2-sided (Automatic)

Send Specifications

Optional/ standard

Standard on all models

Destination

E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV, Mail Box,
Super G3 FAX(Optional), IP Fax(Optional)

Colour Mode

Automatic-Colour Select (Full Colour/Grayscale),
Automatic-Colour Select(Full Colour/Black-and-White),
Full colour, Grayscale, and Black-and-White

Address Book

LDAP (2,000)/Local (1,600)/One-touch (200)

Send Resolution

100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x
400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi

Communication Protocol

File: FTP, SMB, WebDAV
E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard: JPEG, TIFF, PDF/XPS (Compact), PDF/PDF/A-1b,
Optimize for Web, Apply Policy)

Optional: PDF (Trace&Smooth, Encrypted), PDF/XPS
(Digital Signature, Searchable), Office Open XML
(Powerpoint, Word)

Fax Specifications

Optional/ Standard Optional on all models

Maximum Number of Connection Lines 4

Modem Speed Super G3: 33.6 kbps
G3: 14.4 kbps

Compression Method MH, MR, MMR, JBIG

Resolution 400 x 400 dpi, 200 x 400 dpi,
200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size A5 and A5R* to A3
* Sent as A4

FAX Memory Up to 30,000 pages

Speed Dials Max. 200

Group Dials/Destinations Max. 199 dials

Sequential Broadcast Max. 256 addresses

Memory Backup Yes

Store Specifications

Mail Box (Number supported)

100 User Inboxes, 1 Memory RX Inbox,
50 Confidential Fax Inboxes
30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV
Supported Client PC: Windows (Windows Vista/7/8/8.1/10)
Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16GB (Standard HDD)
Approx. 480GB (1TB HDD)

Memory Media

Standard: USB Memory

Security Specifications

Authentication

Standard: Picture Login Authentication, User Authentication,
Department ID Authentication, (Device and Function
Level Login), Access Management System

Optional: My Print Anywhere secure print (Requires uniFLOW)

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock,
Hard Disk Drive Erase, Hard Disk Drive Encryption (FIPS140-2
Validated), Mail Box Password Protection

Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal

Network

Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted
Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP
Authentication, POP Authentication before SMTP

Document

Standard: Secure Print, Force Hold Print
Optional: Encrypted PDF, Encrypted Secure Print, User and
Device signatures, Secure Watermarks, Document
Scan lock

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C (50 to 86 °F)
Humidity: 20 to 80 % RH (no condensation)

Power Requirements

220-240V (±10 %) , 50/60Hz (±2 Hz) , 6Amp

Power Consumption

Maximum: 1.8 kW
Standby: Approx. 67.9 W *

*Reference Value
Sleep mode: Approx. 0.8 W **

**0.8W sleep mode is not available in all circumstances due to
certain settings.

Software and Printer Management

Remote management tools

eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance)

Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.

iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management)

Scanning software

Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.

Platform

MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device.

Document Publishing

iW DESKTOP: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorization.

Paper Supply Options

PAPER SUPPLYING UNIT

Name: CASSETTE FEEDING UNIT-AM1
Paper Capacity: 550 Sheets x 2 Cassettes (80 gsm)
Paper Size: Standard size: A3, B4, A4, A4R, B5, B5R, A5R, Foolscap, India Legal, F4A
Custom size: 98.0 mm x 182 mm to 304.8 mm x 457.2 mm

Paper Weight: 52 to 256 gsm
Power Source/Max. Power Consumption: From the Main Unit
****Dimensions (W x D x H):** 620 mm x 700 mm x 251 mm
****When attached with the Main Unit**
Weight: Approx. 22.5 kg

Name: HIGH CAPACITY CASSETTE FEEDING UNIT-A1
Paper Capacity: 2,450 sheets (80 gsm)
Paper Size: A4
Paper Weight: 52 to 256 gsm
Power Source/Max. Power Consumption: From the Main Unit
****Dimensions (W x D x H):** 620 mm x 700 mm x 251 mm
****When attached with the Main Unit**
Weight: Approx. 30 kg

Name: PAPER DECK UNIT-F1
Paper Capacity: 2,700 sheets (80 gsm)
Paper Size: A4, B5
Paper Weight: 52 to 256 gsm
Power Source/Max. Power Consumption: From the Main Unit
****Dimensions (W x D x H):** 344 mm x 630 mm x 440 mm
Weight: Approx. 31 kg

Output options

INNER FINISHER

Name: INNER FINISHER-H1
Number of Trays: 2
Top Tray Capacity: A4/B5/A5/A5R 45 sheets
A3/B4/A4R/B5R 45 sheets
Lower Tray Capacity: A4/B5/A5/A5R 500 sheets
A3/B4/A4R/B5R 250 sheets
Paper Weight: 52 to 300 gsm
Staple Position: Corner, Double

Staple Capacity: Corner and Double
Stapling: A4/B5: 50 sheets (52 to 90 gsm)
A3/B4/A4R: 30 sheets (52 to 90 gsm)
ECO-Staple: A3/A4/B4/B5: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (81.5 to 105 gsm)
Staple-on-Demand: 40 sheets (80 gsm)

Power Source/Max. Power Consumption: From the Main Unit
Dimensions (WxDxH): 466 mm x 525 mm x 225 mm
Weight: Approx. 8.6 kg

STAPLE FINISHER

Name: STAPLE FINISHER-Y1 (External)
Number of Trays: 2
Top Tray Capacity: A4/B5/A5/A5R 250 sheets
A3/B4/A4R/B5R 125 sheets
Lower Tray Capacity: A4/B5/A5/A5R 3,000 sheets
A3/B4/A4R/B5R 1,500 sheets
Paper Weight: Upper Tray 52 to 256 gsm
Lower Tray 52 to 300 gsm
Staple Position: Corner, Double

Staple Capacity: Corner and Double
Stapling: A4/B5: 50 sheets (52 to 90 gsm)
A3/B4/A4R: 30 sheets (52 to 90 gsm)
ECO-Staple: A3/A4: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (81.5 to 105 gsm)
Staple-on-Demand: 50 sheets (90 gsm)

***Dimensions (W x D x H):** 637 mm x 623 mm x 1,142 mm
****When the extension tray is extended**
Weight: Approx. 31 kg

BOOKLET FINISHER

Name: BOOKLET FINISHER-Y1 (External)
Number of Trays: 2
Top Tray Capacity: A4/B5/A5/A5R 250 sheets
A3/B4/A4R/B5R 125 sheets
Lower Tray Capacity: A4/B5/A5/A5R 3,000 sheets
A3/B4/A4R/B5R 1,500 sheets
Paper Weight: Upper Tray 52 to 256 gsm
Lower Tray 52 to 300 gsm
Staple Position: Corner, Double

Staple Capacity: Corner and Double
Stapling: A4/B5: 50 sheets (52 to 90 gsm)
A3/B4/A4R: 30 sheets (52 to 90 gsm)
ECO-Staple: A3/A4: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (81.5 to 105 gsm)
Staple-on-Demand: 50 sheets (90 gsm)

Booklet Stitch paper size: A3/B4/A4R, Custom Size (195 mm x 270 mm to 304.8 mm x 457.2 mm)
Booklet Stitch Staple Capacity: 20 sheets x 10 sets (52-81.4gsm) (Including 1 cover sheet up to 256 gsm)
***Dimensions (WxDxH):** 637 mm x 623 mm x 1,142 mm
****When the extension tray is extended**
Weight: Approx. 57 kg

PUNCHER UNIT/S

INNER 2/3 HOLE PUNCHER-B1: Two or Three Holes
*Requires INNER FINISHER-H1
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size: Two holes A3, B4, A4, A4R, B5, B5R
Three holes A3, B4, A4, B5
Power Source: From the Main Unit

INNER 2/F4 HOLE PUNCHER-B1: Two or Four Holes
*Requires INNER FINISHER-H1
Acceptable Punch Paper Weight: 52 to 300 gsm

Acceptable Punch Paper Size: Two holes A3, B4, A4, A4R, B5, B5R
Four holes A3, A4
Power Source: From the Main Unit

2/3 HOLE PUNCHER-A1: Two or Three Holes
*Requires either the STAPLE FINISHER-Y1 or BOOKLET FINISHER-Y1

Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size: Two holes A3, B4, A4, A4R, B5, B5R
Three holes A3, B4, A4, B5

Power Source: From the Main Unit

2/F4 HOLE PUNCHER-A1: Two or Four Holes
*Requires either the STAPLE FINISHER-Y1 or BOOKLET FINISHER-Y1

Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size: Two holes A3, B4, A4, A4R, B5, B5R
Four holes A3, A4

Power Source: From the Main Unit

Hardware Accessories

Card Readers

MICARD PLUS PROXIMITY CARD READER
COPY CARD READER-F1
COPY CARD READER ATTACHMENT-B5

Others

TAB FEEDING ATTACHMENT KIT-F1
UTILITY TRAY-B1
INNER 2WAY TRAY-J1

Security Options

Document Security

DOCUMENT SCAN LOCK KIT-B1
SECURE WATERMARK-B1
ENCRYPTED PRINTING SOFTWARE-D1

Data Security

HDD MIRRORING KIT-J1
2.5INCH/250GB HDD-N1
2.5INCH/1TB HDD-P1
REMOVABLE HDD KIT-AL1

System and Controller options

Print Accessories

PCL INTERNATIONAL FONT SET-A1
PCL ASIAN FONT SET-A1

Barcode Printing

BARCODE PRINTING KIT-D1

EFI-Fiery Based Controller

IMAGEPASS-P1
COLOURPASS-GX500
(Applicable for iR-ADV C5550i/C5560i only)

EFI-Fiery Based Controller Options

REMOVABLE HDD DRIVE KIT-B1
FIERY IMPOSE
FIERY COMPOSE
FIERY IMPOSE AND COMPOSE

System Accessories

WEB ACCESS SOFTWARE-K1
SERIAL INTERFACE KIT-K3

FAX Accessories

SUPER G3 FAX BOARD-AS1
SUPER G3 2ND LINE FAX BOARD-AS1
SUPER G3 3RD/4TH LINE FAX BOARD-AS1
REMOTE FAX KIT-A1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1
VOICE GUIDANCE KIT-G1
VOICE OPERATION KIT-D1

Consumables

NPG-71 TONER BK/C/M/Y
NPG-71L TONER BK/C/M/Y
STAMP INK CARTRIDGE-C1
STAPLE-P1
STAPLE CARTRIDGE-Y1

To arrange for a demonstration, simply contact our office below.

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

Canon Singapore Pte. Ltd.
1 Fusionopolis Place # 15-01
Galaxis Singapore 138522

Tel : 65-6799 8888

Fax : 65-6799-8882

www.canon-asia.com

www.canon.com.sg

Partner / Dealer Stamp

This brochure and the specifications of the product have been developed prior to the date of product launch. These specifications are subject to change without notice. Therefore no representations or warranties, either express or implied, are made of the fitness of this product for a particular purpose. In no circumstances shall the information in this brochure be considered part of our terms and conditions of sale. You are advised to check the prevailing specification immediately prior to purchase.

All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners.

uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte Ltd.

0202W887 © 2016 Canon Singapore Pte. Ltd.

All rights reserved. Printed in Singapore.